


CONCLUSION

Applicants respectfully submit that the above-described amendments add no new matter and request their entry into the record.

ABBOTT LABORATORIES
D-377/AP6D-2
100 Abbott Park Road
Abbott Park, Illinois 60064-6050
Telephone: (847) 935-7550
Facsimile: (847) 938-2623

Respectfully submitted,
Ronny van't Oever, *et al.*



Mimi C. Goller
Registration No. 39,046
Attorney for Applicants

VERSION WITH MARKING TO SHOW CHANGES MADE

1. (Amended) A three-dimensional optical method for determining the volume, V, and hemoglobin content, HC, of individual red blood cells, said method comprising the steps of;
 - a) treating an anti-coagulated whole blood sample with a reagent solution, said solution comprising a sphering agent and a neutrally buffered isotonic saline solution;
 - b) passing red blood cells of said sample in single file [a red blood cell isolated from said sample] through a light beam directed along an optical path at a selected wave length;
 - c) measuring the resultant magnitude of a first forward angle light scatter signal, a second intermediate angle light scatter signal, and a third side-angle light scatter signal from each cell;
 - d) projecting a three-dimensional coordinate of said light scatter signals from each cell onto a precalibrated three dimensional surface containing grid lines of V and HC;
 - e) determining the values of V and HC by the location of each projected intercept onto said three dimensional grid surface.

12. (Amended) A three-dimensional optical method for determining the volume, V, and hemoglobin content, HC, of individual red blood cells, said method comprising the steps of;
 - a) treating an anti-coagulated whole blood sample with a reagent solution, said solution comprising a sphering agent and a neutrally buffered isotonic saline solution,;
 - b) passing red blood cells of said sample in single file [a red blood cell isolated from said sample] through a light beam directed along an optical path at a selected wavelength;

- c) measuring the resultant magnitude of one forward angle light scatter signal, one light loss signal, and a third side-angle light scatter signal from each cell;
- d) projecting a three-dimensional coordinate of said light scatter signals from each cell onto a pre-calibrated three dimensional surface containing grid lines of V and HC;
- e) determining the values of V and HC by the location of each projected intercept onto said three dimensional grid surface.